



特点 Feature:

- 1. 双层屏蔽，良好的屏蔽效果-75dB； Double shield, good shielding effect -75dB
 - 2. 良好的温度特性，范围-55~+200℃； Good temperature characteristics, range -55 ~ +200 °C
 - 3. 较低的驻波比，较低插入损耗，低成本； Lower VSWR, lower insertion loss, low cost
- 配接接头： N-J、SMA-J、N-K、SMA-K 四种 Fittings: N-J, SMA-J, N-K, SMA-K

型号 model	VSWR		
	DC~1GHz	1~3GHz	3~6GHz
SMA-J/SMA-J	≤1.10	≤1.15	≤1.2
N-J/N-J	≤1.10	≤1.15	≤1.2
N-K/SMA-K	≤1.10	≤1.15	≤1.2

电缆型号 Cable type	内导体外径 Inner conductor diameter	最大外径 largest diameter	最小弯曲半径 mm Minimum bending radius mm	温度范围 Temperature range	最大工作电压 Maximum working voltage	最高使用频率 highest frequency
RG142	Φ0.94	Φ4.95	25	-55~165	1900	8
损耗 dB/m						电缆保持力 N
100MHz	400MHz	1GHz	3GHz	5GHz	6GHz	
0.135	0.36	0.52	0.95	1.20	1.32	

